

# UF 5000

 **Flexible for Mixed Usage**

 **Free to Scale Up**

 **19 inch Rack Compatible**

 **Ultra Cost effectiveness**



## Module

UF5000

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| Nominal Voltage (VDC)               | 51.2                                 |
| Battery Module Capacity (kWh)       | 5.12                                 |
| Usable Capacity (kWh)               | 4.864                                |
| Dimension (W*D*H mm)                | 442*452.6*161                        |
| Weight(kg)                          | 42                                   |
| Depth of Discharge                  | 95%                                  |
| Charge/ (Normal)                    | 100                                  |
| Discharge (Max)                     | 100                                  |
| (A) (Peak)                          | 121~200@15sec                        |
| Communication port                  | RS485/CAN                            |
| IP rating                           | IP20                                 |
| Single String Quantity (pcs)        | 20                                   |
| Working Temperature/ (°C) Charge    | -10~55                               |
| Working Temperature/ (°C) Discharge | -10~55                               |
| Storage Temperature/ (°C)           | -20~60                               |
| Humidity (RH)                       | 5%~95% No condensation               |
| Short current/duration time (A)     | <2000/1ms                            |
| Altitude (m)                        | ≤4000                                |
| Design life (@25°C)                 | 15years                              |
| Cycle life (@25°C)                  | >6,000                               |
| Certification                       | IEC62619/UN38.3/RoHS/Reach/WEEE/MSDS |